

A standard linear barcode is positioned vertically on the left side of the page. It is composed of vertical black lines of varying widths on a white background. The barcode is used for tracking and identification purposes.

		Subclass
	Class	ISSUE CLASSIFICATION

**PATENT NUMBER**

**U.S. UTILITY Patent Application**

APPLICATION NO.	CONT/PRIOR	CLASS	SUBCLASS	ART UNIT	EXAMINER/NCR
09/756348		702 382	232	2862 T. S. S. S.	Grant

CANTS

## System and method providing improved data compression via wavelet coefficient encoding

PTO-2040  
12/99

## **ISSUING CLASSIFICATION**

Continued on Issue Slip Inside File Jacket

TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.				<b>NOTICE OF ALLOWANCE MAILED</b>	
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent. No. _____				<b>ISSUE FEE</b>	
	(Assistant Examiner)	(Date)		Amount Due	Date Paid
	(Primary Examiner)	(Date)		<b>ISSUE BATCH NUMBER</b>	
<input type="checkbox"/> The terminal _____ months of					

**WARNING:**

The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code Title 35, Sections 122, 181 and 368. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-438A  
(Rev. 6/99)

FILED WITH:  DISK (CBF)  FICHE  CD-ROM

(Attached in pocket on right inside flap)